



Rack PDU 380V DC 8 outlets

Hi-Power version 11.4kW

- Compact 19" design, LED indicator and DC rated fuses.

Description

The Rack PDU PDU830 is a fused DC rated distribution unit with LED indicator, polarity indicator in one compact unit.

Output connectors are locked pluggable SAF-D-GRID connectors for safe cabling in tight rack spaces. 19 inch mounting in standard racks, horizontal or vertical.

The PDU can be used in all versions of the standard ETSI EN 301 605 -Earthed negative, midpoint or high-ohmic.

Input is 3meter cable with DC rated CEE connector.

Features

- DC rated distribution outputs
- LED indicator
 - blown fuse
 - polarity error +/-
- Locked safety connection
- Compact 1U form factor
- Designed for typical A + B redundancy installations



	PDU 830	
Input		
Input voltage range	300 – 400 Vdc	
Input current	Max 30A	
Overload protection	2x32A fuses	
Output		
Output current (total)	Max 30A	
Output current (single output)	Max 10A	
Number of outputs	8	
Monitoring		
LED indicator (green)	Fuses OK	
-"-	Polarity OK	
Mechanical data		
Weight	2 kg	
Width	19 "	
Height	1U	
Depth	80 mm	
Enclosure	IP 20	
Max ambient temperature	30°C	
CE		
Safety	EN/IEC 60950, class 1	
Grounding	ETSI EN 301 605	

*All data preliminary, subject to change.

