

# Rack PDU (IEC)

**Hi-Power version 12kW**  
**Compact "Zero U" design**  
**LED indicator and DC rated fuses**  
**20 IEC standard outlets**

## Description

The Rack PDU 2030\_IEC is a fused, DC rated distribution unit with 20 outlets and LED indicator, all in one compact unit.

Output connectors are the new global IEC standard for direct current.

The PDU can be used in all versions of the direct current standard ETSI EN 301 605  
-Earthed negative, midpoint or high-ohmic grounding.

Input is 3meter cable with DC rated CEE connector.

## Features

- DC rated distribution outlets with IEC standard
- LED indicator, triple function
  - Power ON
  - Fuse OK
  - Polarity OK
- Compact 1U x 1U x 21U
- Designed for typical A + B redundancy installations





PDU 2030_IEC	
<b>Input</b>	
Input voltage range	200 - 400 Vdc
Input current	Max 32A
Overload protection	2x32A fuse
<b>Output</b>	
Output -total	Max 32A
Output power (single output)	2.6 kW
Number of outputs	20
<b>Monitoring</b>	
LED indicator (green)	Power ON
-"-	Fuses OK
	Polarity OK
<b>Mechanical data</b>	
Height	21U
Width	19"
Depth	1U
Weight	6 kg
Enclosure	IP 20
Max ambient temperature	55°C
<b>CE</b>	
Safety	EN/IEC 60950, class 1
Grounding	ETSI EN 301 605

\*All data preliminary, subject to change.

